



602 SPEC/PRO MODIFIED RULES

Revised: November 17, 2020

DISCLAIMER

These rules are in effect as of October 25, 2020. This publication supersedes all previous HAVASU 95 SPEEDWAY rules and rule updates. All competitors, pit crew members and car owners must agree to and sign a code of conduct insuring good sportsmanship amongst other competitors, teams, and car owners. If at any time code of conduct rules have not been followed, promoter and/or race director may disqualify any team, crew member, car owner, and/or family member involved with any specific race team.

HAVASU 95 SPEEDWAY reserves the right to alter or amend the rules and regulations in the interest of safety, cost control, and/or fair competition. It is the responsibility of each competitor to read and understand the contents of these rules. If there is a disagreement or dispute regarding the meaning or application of these rules, the decision of the HAVASU 95 SPEEDWAY Race Director shall prevail.

No expressed or implied warranty of safety shall result from publications of or compliance with these rules and/or regulations. The rules and/or regulations set forth herein are designed to provide for the orderly conduct of HAVASU 95 SPEEDWAY racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules.

No pretense is made for having designed a foolproof set of rules and regulations. The spirit and intent of the rules is the standard by which HAVASU 95 SPEEDWAY events will be governed. The HAVASU 95 SPEEDWAY Race Director is authorized to decide if an equipment change or modification is an attempt to circumvent these rules. The HAVASU 95 SPEEDWAY Race Director can and will disqualify a race car in violation of the spirit and intent of these rules. If this rulebook does not specifically state that you can alter, change, or otherwise modify something on your car, you should consider it a violation of these rules. No part is deemed to have been approved by HAVASU 95 SPEEDWAY by passing through prior technical inspections.

The Race Director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. No expressed or implied warranty of safety shall result from such alteration of specifications. Any interruption or deviation of these rules is left to the discretion of the Race Director. His/her decision is final.

These rules are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator or official. All participants, guest and crew members fully understand that racing is inherently dangerous and that they are exposed to risks of death or serious bodily injury. The participants, guest and crew members voluntarily assume these risks.

SPECIFIC CAR RULES

1. Hoosier 970 tires only
 - Must purchase from track
2. 110 Octane or E85 race fuel only
 - VP 110 available at the track
3. Engine Rules
 - 602 GM crate factory sealed or checked by authorized dealers (1 single carburetor)
 - Open Motor (1 single carburetor) cast iron block-wet sump – 410 cubic inch max
4. Any shock allowed; NO Canisters allowed.
5. Fabricated front stubs (Authorized dealers: Phils Phabrication/Dana Stahl/STR/Howe)
 - Any other clips please call for approval
6. Weight Rules and RPM Rules:
 - Crates – 2500 lbs. 58 Left Side (6200 RPM)
 - Open – 2650 lbs. 57 Left Side (7200 RPM)
7. 15 x 8 Steel Wheels Only
8. No rack and pinion steering
9. Rear Gears (Steel Spools Only)
10. All suspension and steering components MUST be made out of only steel
 - Only Aluminum pars allowed: track bar mounts and sliders (solid links only)
11. Track Width: 78 in. bulge to bulge, front and rear, at ride height
12. Body Rules:
 - Max Rear Deck Width: 68 inch Max
 - Max Rear Deck Height: 38 inch Max
 - Spoiler Dimensions Only: 4 inch x 60 inch wide
 - Front Nose Overhang: 45 inches Max
 - Front Nose Width: 45 ½ inches Max
 - Rear Quarter Panel Overhang: 49 inches max